

LCD Cable Tester



LCD Cable Tester



NEW!



NF-8601

NF-8601/8601W Cable Length Tester

1. Measure length of network telephone and coaxial cable.
2. Identify which pins are providing power and detect how much voltage.
3. To test network performance, data packet, min & max time.
4. Tone trace cable with complete AC Interference Rejection.
5. Port flash directly locate target cable connected to switch/hub/router.
6. To import and export data from computer (160 sets, txt format).
7. 8 remote identifiers help to test 8 cables at one time (Only for NF-8601W).

NF-860W



NF-8601S

TDR Cable Length Tester

1. Measures cable length and display the distance to fault, graphical wire mapping.
2. Identify PoE presence and detect how much voltage.
3. Test network performance, data packet, min & max time.
4. Tone trace cable with complete AC Interference Rejection.
5. Port flash directly locate target cable connected to switch/hub/router.
6. To import and export data from computer (160 sets, txt format).



NF-488

PoE Checker

1. Test the information of the standard PoE device.
2. Identify the supply voltage, power supply polarity and mode of PoE devices.
3. Check physical status of RJ45 cable.
4. Test the current, voltage and power consumed by DC appliances.
5. The loop-back test function of the switch.



NF-8209

Wire Tracker

1. Three scan modes selectable: Digital/Analog/PoE mode.
2. Measure cat5, cat6 cable length, the range is 200m.
3. Port flash function directly find target cables connected with switch.
4. Test physical status for STP, UTP lan cable.
5. Detect AC voltage & PoE.



NF-308S

NF-308S/388 Wire Fault Locator

1. Trace RJ45 RJ11 BNC USB and other cables
2. Port flash directly locate target cable connected to switch
3. Check wiring error in RJ45/BNC cable, such as open, short, cross
4. Measure RJ45 and BNC cable length and broken point
5. Testing polarity and voltage
6. 8 remote identifiers help to test 8 cables at one time (Only for NF-388)



NF-8108A

NF-8108M

NF-8108A/8108M Network Cable Tester

1. Measures cable length and determine the distance of open circuit and short circuit.
2. Permits you to check wiring error in 5E/6E twisted cord network and telephone line.
3. 8 remote identifiers help to test 8 cables at one time (Only for NF-8108M).



NF-300

Network Coaxial Cable Tester

1. Trace RJ45 BNC USB and other cables without AC current noise.
2. Port flash directly locate target cable connected to switch.
3. Check wiring error in RJ45/BNC cable, such as open, short, cross.
4. Measure RJ45 and BNC cable length and broken point.



NF-8200

Network Telephone Cable Tester

1. Trace and locate RJ45 (STP / 4-core), RJ11 cables.
2. Anti-jamming, capable of working on the exchanger and PC startup.
3. Measure cable length for RJ45, RJ11 Cable.
4. Check open, short, cross, crosstalk for RJ11, RJ45 cable.
5. Locate short and breakage point accurately.



NEW

NF-8209S

Wire Tracker

1. Three scan modes selectable: Digital/Analog/PoE mode.
2. Measure cat5, cat6 cable length, the range is 200m.
3. Port flash function directly find target cables connected with switch.
4. Test physical status for STP, UTP lan cable.
5. Detect the crimping condition of the crystal head.
6. Detect AC voltage & PoE.
7. Rechargeable lithium battery.



NEW

NF-8508

Optical Meter Wire Tracer

1. Two scan modes selectable: AC filter /Analog mode, up to 300m.
2. Measure cable (cat5/6) length accurately, the range is 2.5~200m.
3. Hub blink for locating network port by the flashing port light on Hub / Switch. Available to 10M/100M/1000M Hub/switch.
4. It supports to test physical status for STP, UTP lan cable and detect the crimping condition of the crystal head.
5. PoE testing: identify which pins are providing power and detect how much voltage, identify which the type of PSE (all at standard).
6. OPM&VFL: Measure 6 standard wavelengths 850/980/1300/1310/1490/1550/1625/1650nm, test range: -70dBm~+10dBm, 10mw red light source (Check fiber breaks, damaged)



NF-868

LCD Cable Length Tester

1. Test open, short, cross connection, reverse, pairing connection and broken wire positioning.
2. Capable to measure length of RJ45/RJ11/BNC/USB cable at length of 2000m.
3. Cable tracing on switch or router with power-on.
4. To quickly find the target wire or cable among kinds of wires.



NF-858C

Wire Tracker

1. Trace and Measure lan cable and coaxial cable length.
2. CAT5 CAT6 and Coaxial cable continuity test.
3. Port flash directly locate target cable connected to switch.
4. Build in a VFL to check the fiber cable faults.
5. Detect the voltage on POE switch
6. Built-in rechargeable Lithium battery save energy.

Multifunction Wire Tracker



Underground Wire Locator



NEW!

NF-801B



NF-806R

NF-801B/806R

Wire Tracker

1. Tracking RJ11, RJ45, cables or other metal wire.
2. Check wiremap of Lan cable.
3. Transmitter with RJ11 connector and pair of alligator clips(NF-806R).
4. Low Voltage alarm function.

NF-168S



NF-168V

NF-168S/168V

Wire Tracker

1. Check wiremap of Lan cable.
2. Tracing RJ45/RJ11/BNC cable connected to the switch or router (NF-168S).
3. Tracing RJ45/RJ11 cable connected to the switch or router (NF-168V).
4. Visual fault locator: 5mW (NF-168V).
5. Two scan modes selectable: AC filter & Non AC filter.

NF-816



NF-816L

NF-816/NF-816L

Underground Wire Locator

1. Helpful-locating & tracking buried and hidden wires.
2. Easily locate pet fence wires, metals pipes, electrical wires, etc.
3. Wire tracer range-up to 2 feet deep and 1000 feet in length.
4. Power : 9V Alkaline battery (NF-816).
5. Power : Rechargeable Lithium battery (NF-816L).



NF-826

Underground Wire Locator

1. Finds for open or shorts cable in the wall or earth.
2. Tracks for cable in the wall or earth.
3. Finds for fuse and safeguard.
4. Finds for socket or junction box is envelop.
5. Finds for open or shorts conduit under the floor.



NF-811

Wire Tracker

1. Tracking RJ11, RJ45, cables or other metal wire.
2. Check wiremap of Lan cable.
3. Telephone Line Test : Judging TIP or PING line.



NF-810

Wire Tracker

1. Tracking RJ11, RJ45, cables or other metal wire.
2. Check wiremap of Lan cable.
3. Telephone Line Test : Judging TIP or PING line and polarity test.
4. Detect Ethernet network for Power over Ethernet existence.



NF-825TMR

Advance AC Wire Tracker

1. Inspect the wiring condition at the electrical outlet.
2. Locate the correct circuit breaker in a panel corresponding to the circuit.
3. Tone trace live cable find the direction of wires and cables, breakpoints.
4. Cable tracing on switch or router with power-on.
5. Non-contacted voltage detect function.



NF-825MJ

Digital Circuit Breaker Finder

1. Detect wiring faults of open ground, open neutral, open hot, dual open (neutral and ground), reversed hot/ground, and reversed hot/neutral (NF-825M).
2. Locate the correct circuit breaker in a panel corresponding to the circuit.
3. Non-contacted voltage detect function.



NF-802

Wire Tracker

1. Tracking RJ11, RJ45, cables or other metal wire.
2. Check wiremap of Lan cable.
3. Detect the crimping condition of the crystal head.
4. Tone trace cable with complete AC Interference Rejection.
5. Non-contacted voltage detector function.



NF-820

High & Low Voltage Wire Locator

1. Track with complete AC Interference Rejection.
2. Tone trace live cable ($\leq 220V$ with socket avoiding burnout).
3. Detect invisible cable, the range is 0-2M.
4. Signal sensitivity for transmitter and receiver is adjustable.



NF-468V

Cable Tester

1. Check physical status of RJ45 & RJ11 cable.
2. Two modes for power supply : 9V battery or power adaptor.
3. Suitable for Home and office networks.
4. Supports both Network and Telephone cable.



NF-466

Cable Tester

1. Automatically runs all tests and checks.
2. Supports RJ45/RJ11/RJ12/CAT5/CAT6/CAT7 UTP Wire.
3. Portable handheld design. Powered by a 9V Battery.
4. Suitable for Home and office networks.
5. Supports both Network and Telephone cable.

Cable Continuity Tester



Optical Multimeter



NEW!



NF-3468

4-in-1 Network Cable Tester

1. Tests 4 types of cables: RJ45/RJ11/2.0 USB/BNC.
2. LEDs indicate connections and faults.
3. Simple one-button test.
4. Detachable module for testing remote points.



NF-469

Port Flash Cable Tester

1. Check continuity of RJ11 & RJ45 Cable quickly.
2. Port flash directly locate target cable connected to switch/hub/router.
3. Detachable module for testing remote points.



NF-468PF

NF-468PF/468S

Cable PoE Tester

1. Check continuity of RJ11 & RJ45 Cable quickly.
2. Detect Ethernet network for Power over Ethernet existence (NF-468PF)
3. Identify that the standard of the POE switch is 802.3at or 802.3af(NF-468S)
4. Detect the crimping condition of the crystal head(NF-468S)



NF-468S



NF-468

NF-468/468B

Cable Tester

1. Test RJ45 and RJ11 cable (NF-468).
2. Test RJ45 & RJ11 and BNC Cable (NF-468B).
3. Test corresponding double-twisted cable 1, 2, 3, 4, 5, 6, 7, 8, and G.
4. Judge wrong connection, short circuit and open circuit.



NF-468B



NF-900C

Optical Power Meter

1. Measurement of the power of optical sender (dbm and w).
2. Insertion loss test of optical devices.
3. Wavelength: 850/1300/1310/1490/1550/1625nm.



NF-909C

NF-907C

NF-907C/909C

2-in-1 Optical Meter

1. Wavelength: 850/1300/1310/1490/1550/1625nm (power meter)
2. NF-907C Wavelength: 650nm (visual fault locator), 10mW
3. NF-909C wavelength: 1310 / 1550nm (light source)



NF-911C

3-in-1 Optical Multimeter

1. Light source supports 1310 and 1550 nm.
2. Power meter supports 850, 1300, 1310, 1490, 1550 and 1625 nm.
3. Visual fault locator: 20mW.



NF-912

PON Meter

1. APC Connector.
2. Automatic shutdown (can be cancelled).
3. The meter test threshold can be set through the management software.
4. Users can test 1490 in the PON network at the same time nm, 1550nm, 1310nm three wavelengths.

NEW



NF-908



NF-908L



NF-908S

NF-908/908L/908S

Multifunctional Optical Meter

1. Support 850/980/1310/1490/1550/1625nm wavelength
2. Measurement range: -60 to +8dBm.
3. Cable continuity testing function
4. Check fiber breakage, winding, etc(NF-908L/S)
5. Cable tracing function(NF-908S)



NF-271

Laser Distance Meter

1. Length, area, volume and Pythagorean modes.
2. Switch the reference position according to requirement.
3. Store up to 50 sets of data and retrieve historical data.
4. Max range: 50/70m for option.
5. Battery type: 1.5V 2*AAA.



NF-272L

Laser Distance Meter

1. Length, area, volume and Pythagorean modes.
2. Broadcast voice and electronic angle.
3. Switch the reference position according to requirement.
4. Store up to 99 sets of data and retrieve historical data.
5. Max range: 60/80/100m for option.
6. Battery type: rechargeable Lithium battery.

Laser Distance Meter

FANGBE®

Testing Instrument

FANGBE®

NEW!



- NF-273L**
Laser Distance Meter
1. Length, area, volume and Pythagorean modes.
 2. Broadcast voice and electronic angle.
 3. Bluetooth for transferring measurements into desired software.
 4. Switch the reference position according to requirement.
 5. Store up to 99 sets of data and retrieve historical data.
 6. Max range: 60/80/120m for option.
 7. Battery type: rechargeable Lithium battery.



- NF-274L**
Laser Distance Meter
1. Green laser helps measurement in outdoors.
 2. Length, area, volume and Pythagorean modes.
 3. Broadcast voice and electronic angle.
 4. Bluetooth for transferring measurements into desired software.
 5. Switch the reference position according to requirement.
 6. Store up to 100 sets of data and retrieve historical data.
 7. Max range: 60/80/100m for option.
 8. Battery type: rechargeable Lithium battery.



- NF-275L**
Laser Distance Meter
1. Length, area, volume and Pythagorean modes.
 2. Broadcast voice and electronic angle.
 3. Switch the reference position according to requirement.
 4. Green laser helps measurement in outdoors.
 5. Store up to 99 sets of data and retrieve historical data.
 6. Max range: 60/100m for option.
 7. Battery type: rechargeable Lithium battery.



- NF-2240/2260L**
Laser Tape Measurer
1. Tape & Laser measurement.
 2. Length, area and volume modes.
 3. Max range: 40m (NF-2240) & 60m (NF-2260L).
 4. Battery type: 1.5V 2*AAA (NF-2240) & rechargeable Lithium battery (NF-2260L).




- NF-517**
Wall Scanner
1. Locating wood, metal and AC wires hidden in the walls, floors and ceilings of the house.
 2. It can be automatically calibrated anywhere on the wall to successfully find the center of studs in one step.
 3. It has large LCD display and sound alarm, which can detect the exact location of the objects.



- NF-518/NF-518S**
Wall Scanner
1. Wall Detecting Function: Metal Detection/Wooden Detection/AC Wire Detection.
 2. Depth measurement: Wood: 3.8cm/ Live (AC) wire: 5cm/ Non-magnetic metal: 10cm/ Magnetic metal: 12cm.
 3. Laser rangefinder: 60m/Distance/Area/Volume/Pythagorean measurement (NF-518S).
 3. Equipped with automatic shutdown function.
 4. Equipped with a 2.4-inch high-definition color screen, the test results are clearly displayed.



NF-112G



NF-15T

Function comparison (Laser level)

Model	NF-112G	NF-15T
Laser Beam	Green	Green
Specifications	4V4H4D(3D12 lines)	4V1H1D(5 lines)
Laser Diode Wave Length	635nm	635nm
Working Range	25m	30~50m
Automatic Leveling Range	±3°	±3°
Power Supply	Lithium battery	Lithium battery
Accuracy	±2mm/5m	±1mm/3m
Operating Temp	-10℃~45℃	-10℃~50℃
Laser Level Weight	1.85kg	1.4kg



NF-521



NF-521S

NEW

NF-521/521S Thermal Imager

1. High-precision infrared camera capable of real-time image transmission.
2. Center temperature measurement and high temperature tracking.
3. Wide Application Range, such as schools, factories, office buildings.
4. Infrared Image Resolution: 32°32, 1024pixels (NF-521) & 120°90, 10800 pixels (NF-521S).

Testing Instrument

FANGBE

Air Quality Tester

FANGBE

NEW!



NF-583S/NF-586S Smartphone Thermal Imager

1. Resolution:160°120(NF-583)/256°192(NF-586) , Frame rate:25Hz
2. Temperature range:-15°C ~600°C, Wavelength: 8~14um.
3. Temperature measurement method:Point, line, surface temperature measurement
4. Plotting tool:Android4.3 and above mainstream mobile phones
5. Product interface:USB type-C

NF-IPC715 CCTV Tester

It is used for the installation and maintenance of IP network camera and coaxial HD surveillance camera and other security equipment. The tester uses a 5-inch 1280x800P high-definition touch screen. Support max 12MP IP camera and max 4K 8MP coaxial HD camera test; multiple professional tests are built-in APP, compatible with more than 90% of existing brand cameras. Support POE, W-I-F-I, RJ45TDR, DC12V power output etc.



NF-188/198 GPS Land Meter

1. Measure area and length of any shape.
2. Vehicle-carrier & Equal-width area measurement.
3. Display measuring value, figure track after measurement.
4. Height and barometric pressure and satellite measurement (NF-198)

NF-IPC716ADHS CCTV Tester

It is used for the installation and maintenance of IP network camera and coaxial HD surveillance camera and security system. The tester uses a 7-inch 1280x800P high-definition touch screen. Support max 12MP IP camera and max 4K 8MP coaxial HD CVI TVI AHD SDI CVBS camera test; Support Cable RJ45 TDR Test, POE, W-I-F-I, DC 5V 2A/12V 3A/24V 2A power output; Multiple professional tests are built-in APP, compatible with more than 90% of existing brand cameras.



NF-5120/5130/5140 Pipe Blockage Detector

1. Locate hidden blockage, clogging inside the pipe.
2. Waterproof probe, IP54 and sensitivity adjustment.
3. Rechargeable lithium battery.
4. Optional from 20/30/40M.



NF-904 Visual Fault Locator

1. Detect and locate fiber breaks, poor connections, bending or cracking.
2. The 2.5mm universal connector of the detector is compatibly designed for ST, SC, FC
3. Optional from 5/10/20/30M.



JMS10/JMS11 Air Quality Monitor

1. Test items: formaldehyde and TVOC in the air (including benzene).
2. Detection range: 0~9.999 mg/m3 (formaldehyde) 0~2.888 mg/m3(TVOC).
3. Detection principle: principle of semiconductor gas sensor.
4. Sampling method: diffusion collection.



JMS12/JMS12C Air Quality Monitor

1. TVOC detect Scope:0~2.888mg/m³
2. HCHO detect Scope:0~9.999mg/m³
3. Temperature detect Scope: -30~60°C +/-1°C
4. Humidity detect Scope: 0~99%RH +/-1%
5. CO2 detect Scope:0~5000ppm (only for JMS12C)
6. Types of batteries: 1*lithium battery*700mAh



JMS13 PM2.5 Air Detector

1. TVOC detect Scope:0~2.888mg/m³
2. HCHO detect Scope:0~9.999mg/m³
3. Temperature detect Scope: -30~60°C +/-1°C
4. Humidity detect Scope:0~99%RH +/-1%
5. PM2.5/10 detect Scope:0-1000 ug/m³
6. Types of batteries: 1*lithium battery*1400mAh



JMS15 Digital Temperature Meter

1. Temperature and Humidity Functions: With temperature range from -20 °C to +50 °C and humidity 10 % ~ 99 % RH, temperature and humidity readings show directly.
2. Time Function: Besides the basic time display, these item also has alarm clock and calendar display (month and date).
3. Memory Function: When pushing the button MEMORY, it could display the memory of temperature and humidity maximum and minimum.



JMS16 4-in-1 Air Detector

1. TVOC detect Scope:0~2.888mg/m³
2. HCHO detect Scope:0~9.999mg/m³
3. Temperature detect Scope: -30~60°C +/-1°C
4. Humidity detect Scope: 0~99%RH +/-1%
5. CO2 detect Scope:0~5000ppm
6. PM2.5/10 detect Scope: 0-1000 ug/m³
7. Types of batteries: 1*lithium battery*1400mAh



AT68/JMS25 Alcohol Tester

1. Detect alcohol level in your body in seconds, providing you with high-precision test results.
2. Great for wedding, parties or other social activities, ensures your safe driving after drinking.

Detectors & Meters

FANGBE®

Digital Microscope

FANGBE®

NEW!

NEW



JMS110

Camera Detector

Designed for Privacy Protection, detect wired and wireless hidden cameras, pinhole cameras, eavesdropping devices, GPS locators and etc.

NEW



NF-562

Noise tester

It's a professional noise tester with portable size, stable functionality, the device can direct, accurate and fast test the decibel level in any environment; Mainly used in construction field, entertainment venue, living community etc to monitor the noise level of the environment.

NEW



NF-563

Handheld Temperature and Humidity Detector

It can accurately and quickly display the temperature and humidity of the environment. It is mainly used for monitoring various environments such as indoor environment, warehouse, and outdoor weather.

NEW



NF-565

Digital Pressure Gauges Manometer

It can measure differential pressure / positive pressure / negative pressure, with the following optional measurements: Unit: kPa, mmHg, inHg, psi, mbar, bar, ozin, kgcm, inH O, ftH O, cmH O with simple hose connection for ventilation and air conditioning system measurement and field verification. Or any gas pressure system failure of the overhaul. Operation and maintenance engineers and scientific researchers indispensable measurement tools. It is mainly used for monitoring various environments such as indoor environment, warehouse, and outdoor weather.

NEW



ZSB-02

Digital Hour Meter

1. When engine is off, display shows total run time of engine and remains visible.
2. Total Hours reading displays from 0 to 99,999 Hours, 0.1 hours accuracy.
3. Total hours can be reset.

NEW



RL-HM016H

Digital Hour Meter

1. Vibration hour meter accumulative total running time TOT, total time cannot be reset.
2. Timing range: 0-99999H, 0.1H accuracy.
3. Recording partial running time PAR, for example: maintenance and oil change reminder service, reset-able.
4. Waterproof rate: IP68



G1200

Digital Microscope

1. Screen size: 7 inches
2. Screen resolution: 1024X600
3. Screen saver: Off-30 sec-1min-2 min (optional)
4. Automatic shutdown: Off and 3/5/10minutes
5. Hz light source: 50 Hz-60 Hz
6. Language options: 16 Languages
7. Date adjustment: year, month, day / hour, minute, second
8. Format & Default: YES/No.

NEW



G600

Digital Microscope

1. Pixel: HD 3.6MP CCD
2. Display: 4.3 inches HD LCD display.
4. Magnification: 1-600X continuous magnification system.
5. Object distance: 15mm-- infinity
6. With built-in lithium battery, Continuous working for 8 hours .
7. Languages: 16 Languages available

NEW



317

Digital Microscope

1. Screen Size: 4.3 inch TFT panel
2. Magnification: 50-1000X
3. Resolution: 1080P
4. Adjustable Brightness: 8 LED lights
5. For Focus mode/range: Manual/3-40mm
6. Operating system: IOS, Android, Win7/8/10, MacOS
7. Mode: File storage & Photo / Video Capture

NEW



P100

Handheld Endoscope

1. Cable length: 2m/5m/10m Rigid cable
2. Monitor: 2.4-inch Full Color IPS screen
3. Camera resolution: 1280*720, 1920*1080
4. Horizontal viewing angle: 70°
5. Focal length: 5-10cm for front Camera, 2-6CM for side camera.
6. Waterproof level: IP68 (only for lens cable)
7. Battery: 3.7V, 2600mAh lithium

112-2

Handheld Endoscope

1. 1080P HD Endoscope camera with a 4.3-inch color LCD screen that allows you more convenient to perform live analysis on your application area and to view HD photos and videos instantly.
2. IP67 waterproof, six adjustable LED lights to ensure a clear image even under dark conditions. Long focal distance (1.6 inch-198 inch) makes inspections easier. 5M Semi-Rigid cable is both stiff and flexible. Rechargeable battery, a full charge can work up to 3-4 hours.
3. It is widely used in car maintenance, mechanical inspection, pipe repair, household appliance inspection, house maintenance, wall structure inspection, sewer/ drain inspection, etc.

2023 FANGBEI New Products

FANGBEI®



MICRO-280

Battery Tester

1. Use for all batteries 12V 24V with 100~2000 CCA lead-acid batteries.
2. Check the overall health of the battery including the cranking test, and run a complete system charging test.
3. View and Print the test results, and Language selection.



PMB05

Watt Meter

1. This power meter socket has 7 monitoring modes for multiple data monitoring, real-time monitoring of your home appliances consumption for energy and money saving.
2. Compact size design for space-saving, ideal for many appliances, such as computer, air conditioner, refrigerator, dishwasher, microwave oven, etc.



N30

Electric Screwdriver

1. Automatic & Manual Operation: With electric torque of 0.4-0.5N.m and a manual torque of 3N.m.
2. 3 LED Lights: With a dependent light switch, which can illuminate in all directions without rotating.
3. Widely for repairing electronic devices such as smart phone, RC Model, joystick, computer, drone, camera, laptop, keyboard, glasses, watch, small handheld devices and so on.



CS2001A

Electric Screwdriver

1. Can be used for furniture/electrical appliances/digital products/DIY.
2. Can be used for travel tools, etc.
3. Can be used for large and small home appliances, etc.
4. Can be used for large and small household appliances, etc.



GM998/ET330

Coating Thickness Gauge

1. Principle: Magnetic induction (Probe F)/Eddy current (probe N).
2. Range: 0~1500um (0~59.1mil).
3. Accuracy: $\pm(3\%+2um)/\pm(3\%+0.08mil)$.
4. Resolution: 0.1um/0.01mil.
5. Calibration: Zero point/multi-points/Units: um, mil.
6. Min measuring area: diameter 6mm.
7. Min thickness of substrate: 0.5mm (probe F)/0.3mm (probe N).
8. Minimum detectable galvanized layer thickness in Fe+Zn: 15um (ET-330).
9. The maximum distance from the galvanized layer in Fe+Zn: 200um (ET-330).



TR-01 / TR-02

Soil Tester

1. 3-in-1, PH, light intensity, humidity (TR-01).
2. 4-in-1, TR-01 + temperature (TR-02).

2023 FANGBEI New Products

FANGBEI®

NEW!

NEW



LW-G1200



KA600AG



LW-SPI1200

LW-G1200/SPI1200/KA600AG

Golf/Hunting Rangefinder

1. Scan Mode, can be used to range measurement of all items within the scope of application.
2. Golf Mode, design for golf sports specifically, pin-seek, flag-lock, Slope Distance Correction.
3. Speed Mode, this mode is ideal for hunting or other outdoor sports.
4. Measuring range: LW-G1200/LW-SPI1200 (1200M), KA600AG (600M).

NEW



HT641B



HT650B



HT650C

HT641B+/HT650B/HT650C

Infrared Thermometer

- Measurement range: -50°C~600°C/-50°C~550°C/-50°C~800°C
- It's perfect for making a pizza, tempering chocolate, meat, and BBQ.
- You can also measure AC vents, refrigerators, and car engines with it.

NEW



DIGI-318



DIGITAL-PRO-1



DIGI-160

DIGI-160/DIGI-318/DIGITAL-PRO-1

Measuring distance wheel

1. Max measurement range: 99999.9 M / 99999.9 ft
2. Measurement accuracy: $\pm 0.5\%$
3. Min display value: 0.1m/0.3ft
4. Suitable temperature: -10°C~45°C
5. Wheel diameter: 159mm (DIGI-160)/318mm (DIGI-318 & DIGITAL-PRO-1)
6. Unit of measurement: m/ft
7. Product extension length: 1030mm (DIGI-160)/1060mm (DIGI-318 & DIGITAL-PRO-1)
8. Product shrinkage length: 640mm

2023 FANGBEI New Products

FANGBEI

NEW



EZ-9908



EZ-9909SP



C-600

EZ-9908/EZ-9909SP/C-600

Water Quality Tester

1. 4-in-1, PH, TDS total soluble solids in water, TEMP temperature, EC conductivity (EZ-9908)
2. 5-in-1, EZ-9908 + EC conductivity, SALT salinity (EZ-9909SP)
3. 7-in-1, EZ-9909SP + SG seawater density, ORP redox (C-600)

Network tool kits

NF-1206



NF-1304



NF-1501



NEW



HHT904

Travel Adapter

1. It has 3 USB A and 1 Type C Smart Charging Port. Charge up to 4 devices at the same time in just one outlet!
2. Works everywhere in the world, including the nations most traveled and is great for all European outlets.
3. Input Voltage: 100V~240V AC, 50/60Hz
4. Power Rating: 100V~240Vac, 8A Max, 800W~1920W
5. USB output: 5V/3.5A (3A MAX Per USB Port) 3A MAX Per USB C Port)

NEW



HT61

Gas Leak Detector

1. The unit can detect all types of combustible gas like methane, propane, natural gas, etc.
2. As the concentration goes up, the audible alarm beep more frequently and the scale add up.
3. Check appliances and piping in your house to pinpoint the precise source of a potential gas leak with the practical mini gas detector.

2023 FANGBEI New Products

FANGBEI

NEW!

NEW



Multimeter Function Comparison

Model	NF-5310B	NF-5320A	NF-5320D	NF-5330A	NF-5330C
DC Voltage	1000V ± (0.5%+4)	6V 1000V ± (0.5%+4)	6V 1000V ± (0.5%+4)	0.1V~1000V ± (0.5%+3)	0.1V~1000V ± (0.5%+3)
AC Voltage	700V ± (0.5%+4)	6V-750V ± (0.8%+3)	6V-750V ± (0.8%+3)	0.1V~750V ± (0.5%+3)	0.1V~750V ± (0.5%+3)
DC Current		600μA~10A ± (0.8%+8)	6A~10A ± (0.8%+8)		
AC Current		600μA~10A ± (1.0%+8)	6A~10A ± (1.0%+8)		
Resistance	60MΩ ± (0.8%+5)	600Ω~40MΩ ± (1.0%+8)	600Ω 60MΩ ± (1.0%+8)	0.1Ω~60MΩ ± (0.8%+3)	0.1Ω~60MΩ ± (0.8%+3)
Capacitance	60mF ± (3.5%+20)	60nF~6mF ± (5.0%+10) 30mF ± (5.0%+10)	60nF~6mF ± (2.5%+60) 30mF ± (5.0%+10)	10pF~60mF ± (3.5%+20)	10pF~60mF ± (3.5%+20)
Frequency	✓	10Hz 10MHz ± (0.01%+5)			0.01Hz 8MHz ± (0.01%+3)
Duty Cycle	1%-99%±(1.0%+2)	0.1%-99%			
Display counts	6000 counts	6000 counts	6000 counts	6000 counts	6000 counts
Auto/Manual range	Auto	Manual	Manual	Auto	Auto
LED Display	✓	✓	✓	✓/touch button	✓/touch button
Live Test	✓	✓	✓	✓	✓
NCV	✓	✓	✓	✓	✓
Diode test	✓	✓	✓	✓	✓
Continuity	✓	✓	✓	✓	✓
MAX/MINhold	MAX	MAX	MAX	MAX	MAX
Data Hold	✓	✓	✓	✓	✓
True RMS	✓	✓	✓	✓	✓
Battery test(1.5 V/9 V)	✓	✓	✓	✓	✓
Low battery indication	✓	✓	✓	✓	✓
AUTO power off	✓	✓	✓	✓	✓
Double color backlight	✓	✓	✓	✓	✓
Flashlight	✓	✓	✓	✓	✓
Power	1*1.5VAA	2*1.5VAA	2*1.5VAA	2*1.5VAA	2*1.5VAA

Certifications for products



"FANGBEI" Trademarks

